



Dyn-O-Wrap

Dyn-O-Wrap is a self-adhesive film which can protect uninstalled duct sections from the intrusion of contaminants. While duct is handled, stored, or transported its interior is unprotected from water, dust and debris. Dyn-O-Wrap applied over the openings will securely seal the duct and block this exposure. With adhesion strong enough to resist separating from the duct during transportation, the film is easily removed when necessary without leaving any residue. Dyn-O-Wrap is 40% thicker than most other wraps on the market and the extra thickness ensures greater puncture resistance and durability.

FEATURES

- 40% thicker than most other duct wrapping films
 - Durable and puncture resistant
 - Self-adhesive inner surface
 - Excellent adhesion to ductwork
- Easily removable without leaving residue
 - Tinted blue for high visibility

SPECIFICATIONS

• Application: Galvanized Steel, Stainless Steel, Aluminum	• Color: Blue
• Tensile Strength: Minimum 10 psi	• Thickness: 3 mil
• Elongation: Twice its original length	• Disposal: Recyclable
• Weathering: UV resistant and waterproof	

Ordering Information

Item #	Code	Description	Dimensions (cxw)	Weight per roll (lbs.)	Packaging
13380	DW24-200	Dyn-O-Wrap Roll 24" x 200'	24" x 200'	6	6 Rolls/Box
13384	DW36-200	Dyn-O-Wrap Roll 36" x 200'	36" x 200'	9	1 Roll/Box

Sold Per Box Only

Duro Dyne East Division, Bay Shore, NY 631-249-9000 Fax: 631-249-8346
 Duro Dyne Midwest Division, Fairfield, OH 513-870-6000 Fax: 513-870-6005
 Duro Dyne West Division, Santa Fe Springs, CA 562-926-1774 Fax: 562-926-5778
 Duro Dyne Canada, Lachine, Quebec, Canada 514-422-9760 Fax: 514-636-0328
 www.durodyne.com E-mail: durodyne@durodyne.com

