

## Flex Duct - Insulated

### Series 030: R-4



SKU	Description	U/M
A52530	ATCO 5"x25' R4 030SERIES INSULATED FLEX DUCT (BLACK JACKET)	ft
A62530	ATCO 6"x25' R4 030 SERIES INSULATED FLEX DUCT (BLACK JACKET)	ft
A72530	ATCO 7"x25' R4 030 SERIES INSULATED FLEX DUCT (BLACK JACKET)	ft
A82530	ATCO 8"x25' R4 030 SERIES INSULATED FLEX DUCT (BLACK JACKET)	ft
A92530	ATCO 9"x25' R4 030 SERIES INSULATED FLEX DUCT (BLACK JACKET)	ft
A102530	ATCO 10"x25' R4 030 SERIES INSULATED FLEX DUCT (BLACK JACKET)	ft
A122530	ATCO 12"x25' R4 030 SERIES INSULATED FLEX DUCT (BLACK JACKET)	ft
A142530	ATCO 14"x25' R4 030 SERIES INSULATED FLEX DUCT (BLACK JACKET)	ft
A162530	ATCO 16"x25' R4 030 SERIES INSULATED FLEX DUCT (BLACK JACKET)	ft
A182530	ATCO 18"x25' R4 030 SERIES INSULATED FLEX DUCT (BLACK JACKET)	ft
A202530	ATCO 20"x25' R4 030 SERIES INSULATED FLEX DUCT (BLACK JACKET)	ft

Series 080 flex is a UL 181, Class 1 Air Duct, constructed of a tough, black double-ply polyester inner core, surrounded by a thick blanket of fiberglass insulation, durable black polyethylene vapor barrier with spiral reinforcement providing an R-4 rating. Maximum positive operating pressures are 6" w.g. for 4" through 12" diameters, and 4" w.g. for 14" through 20" diameters. Maximum negative operating pressure is 3/4" w.g. for all diameters.

### Series 070: R-4.2



SKU	Description	U/M
A42570	ATCO 4"x25' R4 070 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A52570	ATCO 5"x25' R4 070 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A62570	ATCO 6"x25' R4 070 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A72570	ATCO 7"x25' R4 070 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A82570	ATCO 8"x25' R4 070 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A92570	ATCO 9"x25' R4 070 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A102570	ATCO 10"x25' R4 070 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A122570	ATCO 12"x25' R4 070 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A142570	ATCO 14"x25' R4 070 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A162570	ATCO 16"x25' R4 070 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A182570	ATCO 18"x25' R4 070 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A202570	ATCO 20"x25' R4 070 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft

Series 070 flex is a UL 181, Class 1 Air Duct, constructed of a tough, black double-ply polyester inner core, surrounded by a thick blanket of fiberglass insulation, double-ply metalized grey polyester vapor barrier with spiral reinforcement providing an R-4.2 rating. Maximum positive operating pressures are 6" w.g. for 4" through 12" diameters, and 4" w.g. for 14" through 20" diameters. Maximum negative operating pressure is 3/4" w.g. for all diameters.

### Series 076: R-6



SKU	Description	U/M
A62576	* ATCO 6"x25' R6 076 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A82576	* ATCO 8"x25' R6 076 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A102576	* ATCO 10"x25' R6 076 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A122576	* ATCO 12"x25' R6 076 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A142576	* ATCO 14"x25' R6 076 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A162576	* ATCO 16"x25' R6 076 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A182576	* ATCO 18"x25' R6 076 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft

Series 076 flex is a UL 181, Class 1 Air Duct, constructed of a tough, black double-ply polyester inner core, surrounded by a thick blanket of fiberglass insulation, double-ply metalized grey polyester vapor barrier with spiral reinforcement providing an R-6 rating. Maximum positive operating pressures are 6" w.g. for 4" through 12" diameters, and 4" w.g. for 14" through 20" diameters. Maximum negative operating pressure is 3/4" w.g. for all diameters.

## Flex Duct - Insulated

### Series 078: R-8



SKU	Description	U/M
A42578	ATCO 4"x25' R8 078 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A52578	ATCO 5"x25' R8 078 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A62578	ATCO 6"x25' R8 078 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A72578	ATCO 7"x25' R8 078 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A82578	ATCO 8"x25' R8 078 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A92578	ATCO 9"x25' R8 078 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A102578	ATCO 10"x25' R8 078 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A122578	ATCO 12"x25' R8 078 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A142578	ATCO 14"x25' R8 078 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A162578	ATCO 16"x25' R8 078 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft
A182578	ATCO 18"x25' R8 078 SERIES INSULATED FLEX DUCT (GREY JACKET)	ft

Series 078 flex is a UL 181, Class 1 Air Duct providing an R-8 rating. It is constructed with a double lamination of tough polyester, which encapsulates a steel wire helix and forms the airtight inner core. The double layer core is wrapped in a thick blanket of fiberglass insulation and sheathed in a rugged and durable tri-directional scrim reinforced grey polyester jacket.

### Series 031: R-8



SKU	Description	U/M
A525R8	ATCO 5"x25' R8 031 SERIES INSULATED FLEX DUCT (FOIL JACKET)	ft
A625R8	ATCO 6"x25' R8 031 SERIES INSULATED FLEX DUCT (FOIL JACKET)	ft
A725R8	ATCO 7"x25' R8 031 SERIES INSULATED FLEX DUCT (FOIL JACKET)	ft
A825R8	ATCO 8"x25' R8 031 SERIES INSULATED FLEX DUCT (FOIL JACKET)	ft
A925R8	ATCO 9"x25' R8 031 SERIES INSULATED FLEX DUCT (FOIL JACKET)	ft
A1025R8	ATCO 10"x25' R8 031 SERIES INSULATED FLEX DUCT (FOIL JACKET)	ft
A1225R8	ATCO 12"x25' R8 031 SERIES INSULATED FLEX DUCT (FOIL JACKET)	ft
A1425R8	ATCO 14"x25' R8 031 SERIES INSULATED FLEX DUCT (FOIL JACKET)	ft
A1625R8	ATCO 16"x25' R8 031 SERIES INSULATED FLEX DUCT (FOIL JACKET)	ft
A1825R8	ATCO 18"x25' R8 031 SERIES INSULATED FLEX DUCT (FOIL JACKET)	ft

Series 031 flex is a UL 181, Class 1 Air Duct, constructed of a tough, black double-ply polyester inner core, surrounded by a thick blanket of fiberglass insulation, double-ply metalized polyester vapor barrier which is spiral reinforced providing an R-8 rating. Maximum positive operating pressures are 6" w.g. for 4" through 12" diameters, and 4" w.g. for 14" through 18" diameters. Maximum negative operating pressure is 3/4" w.g. for all diameters.



SKU	Description	U/M	List
A310050	ATCO 3"x100' 050 SERIES UNINSULATED FLEX DUCT	ft	\$1.34
A410050	ATCO 4"x100' 050 SERIES UNINSULATED FLEX DUCT	ft	\$1.41
A102550	ATCO 10"x25' 050 SERIES UNINSULATED FLEX DUCT	ft	\$3.12
A122550	ATCO 12"x25' 050 SERIES UNINSULATED FLEX DUCT	ft	\$3.89
A142550	ATCO 14"x25' 050 SERIES UNINSULATED FLEX DUCT	ft	\$4.72

Series 050 flex is an un-insulated, UL 181 Class 1 Air Duct connector, constructed of a triple lamination of metalized polyester, aluminum foil, and polyester film, encapsulating a steel wire helix.

## Flex Duct - Connectors

## Flex Duct - Uninsulated

### Series 050



SKU	Description	List
N5S3	5" S3 SPOOLS GALVANIZED	\$5.38
N6S3	6" S3 SPOOLS GALVANIZED	\$5.89
N7S3	7" S3 SPOOLS GALVANIZED	\$6.66
N8S3	8" S3 SPOOLS GALVANIZED	\$6.98
N9S3	9" S3 SPOOLS GALVANIZED	\$7.20
N10S3	10" S3 SPOOLS GALVANIZED	\$8.87
N12S3	12" S3 SPOOLS GALVANIZED	\$12.22
N14S3	14" S3 SPOOLS GALVANIZED	\$15.60
N16S3	16" S3 SPOOLS GALVANIZED	\$16.11

## Flex Duct - Accessories



SKU	Description	Sold As	U/M	List
DDDN11	11" BLACK CABLE TIE STRAPS (100/PACK)	1	pk	\$9.00
DDDN36	36" TIE STRAPS (50 PER PACK)	1	pk	\$26.00
DDDN48	48" TIE STRAPS (50 PER PACK)	1	pk	\$56.30
DDS	DURODYNE 1 1/2"x200' VINYL STRAP	1	ct	\$43.80
P050	1-3/4"x300' VINYL STRAP	1	Roll	\$31.62
STRAPDISP	DISPENSER FOR 1-3/4" STRAPPING			\$51.72
GW18	18GA GALVANIZED WIRE 330' ROLL	1	Roll	\$17.92
MFDC1	FLEX DUCT CUTTER			\$77.16
MTY4	MALCO TENSIONING TOOL FOR TIE STRAPS			\$68.66
MTY6	MALCO ADJUSTABLE TIE STRAP TENSIONER			\$97.22
N300	NELCO TENSIONING TOOL FOR TIE STRAPS			\$55.40
CLAMP4	STAINLESS STEEL CLAMP & SCREW - FITS 3.5" - 4.375"			\$3.72
CLAMP5	STAINLESS STEEL CLAMP & SCREW - FITS 3.5" - 5.375"			\$4.04
CLAMP7	STAINLESS STEEL CLAMP & SCREW - FITS 5.125" - 7"			\$4.76
CLAMP8	STAINLESS STEEL CLAMP & SCREW - FITS 7.625" - 8.5"			\$5.26
CLAMP10	STAINLESS STEEL CLAMP & SCREW - FITS 9.875" - 10.75"			\$6.02
CLAMP12	STAINLESS STEEL CLAMP & SCREW - FITS 11.375" - 12.25"			\$6.28

## Stretchflex



SKU	Description	U/M	List
W315	3"x15' ALUMINUM STRETCHFLEX UL APPROVED	ft	\$1.36
W415	4"x15' ALUMINUM STRETCHFLEX UL APPROVED	ft	\$1.80
W515	5"x15' ALUMINUM STRETCHFLEX UL APPROVED	ft	\$2.24
W615	6"x15' ALUMINUM STRETCHFLEX UL APPROVED	ft	\$2.72
W715	7"x15' ALUMINUM STRETCHFLEX UL APPROVED	ft	\$3.16
W815	8"x15' ALUMINUM STRETCHFLEX UL APPROVED	ft	\$3.64
W1015	10"x15' ALUMINUM STRETCHFLEX UL APPROVED	ft	\$4.56
W1215	12"x15' ALUMINUM STRETCHFLEX UL APPROVED	ft	\$5.44